

POWER SERVICE PRODUCTS, INC.
SAFETY DATA SHEET



SECTION 1 - IDENTIFICATION

PRODUCT NAME: CLEAR-DIESEL FUEL AND TANK CLEANER

Unless otherwise noted, all sections of this SDS apply to each of the following products and part numbers.

PART NUMBERS:

9216-06, 9216-09, 9225-06, 9225-09, 9280-06, 19216-06, 19216-09, 19225-06, 19280-06

COMPANY IDENTIFICATION:

Power Service Products, Inc.
P.O. Box 1089
Weatherford, TX 76086
Email: psp@powerservice.com
Phone: 800/643-9089 or 817-599-9486
Fax: 817-599-4893

EMERGENCY PHONE NUMBER: Within USA 1-800-424-9300. Outside USA 001-703-527-3887 (Call Collect).

RECOMMENDED USES: Diesel fuel additive

SECTION 2 – HAZARD(S) IDENTIFICATION

CLASSIFICATION UNDER 29 CFR 1910.1200(d)

(NC=product does not meet classification criteria)

Health Hazard Criteria	Category
Acute Toxicity, Oral:	NC
Acute Toxicity, Dermal:	3
Acute Toxicity, Inhalation, Vapors:	3
Skin Corrosion/Irritation:	2
Serious Eye Damage/Eye Irritation:	2
Respiratory Sensitization:	NC
Skin Sensitization:	NC
Germ Cell Mutagenicity:	NC
Carcinogenicity:	NC
Reproductive Toxicity:	NC

Health Hazard Criteria	Category
Specific Target Organ Toxicity, Single Exposure:	3
Specific Target Organ Toxicity, Repeated or Prolonged Exposure:	NC
Aspiration Hazard:	1

Physical Properties Criteria	Category
Explosives:	NC
Flammable Gases:	NC
Flammable Aerosols:	NC
Oxidizing Gases:	NC
Gases Under Pressure:	NC
Flammable Liquids:	3
Flammable Solids:	NC
Self-Reactive Chemicals:	NC
Pyrophoric Liquids:	NC
Pyrophoric Solids:	NC
Self-Heating Chemicals:	NC
Chemicals Which, in Contact with Water, Emit Flammable Gases:	NC
Oxidizing Liquids:	NC
Oxidizing Solids:	NC
Organic Peroxides:	NC
Corrosive to Metals:	NC

LABEL SIGNAL WORD, HAZARD STATEMENTS, SYMBOLS AND PRECAUTIONARY STATEMENTS UNDER 29 CFR 1910.1200(f):

Please see the Note regarding product labeling in Section 16.

Signal Word(s): **Danger**

Hazard Statement(s): Toxic if inhaled. Toxic in contact with skin. May be fatal if swallowed and enters airways. Causes skin and serious eye irritation. May cause respiratory irritation. Flammable liquid and vapor.



Symbols:

Precautionary Statement(s): Keep away from flames and hot surfaces. No smoking. Do not breathe vapors. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof pumps when pumping. Use non-sparking tools. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Avoid breathing vapors. Wash hands thoroughly after handling. Do not eat, drink or smoke when using

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Page 2 of 10

this product. Wear protective gloves/clothing and eye protection. Store locked up and in a well ventilated place. Keep cool. KEEP OUT OF REACH OF CHILDREN.

Hazards Not Otherwise Classified: None

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Specific chemical information is being withheld as a Trade Secret. Specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200.

The specific chemical identity and exact concentration percentage has been withheld as a Trade Secret.

INGREDIENTS CLASSIFIED AS HEALTH HAZARDS

Chemical Name	Common Name/Synonyms	CAS Number	Concentration (%)
Hydroxy alkoxylate	trade secret	trade secret	35 - 95
Petroleum Distillates	trade secret	trade secret	20 - 50
2,6-di-tert butylphenol	trade secret	trade secret	0.1 – 1.0
Amines	trade secret	trade secret	0.1 – 0.5

SECTION 4 - FIRST AID MEASURES

As a precaution, exposure to liquids, vapors, mists and fumes should be minimized.

EYE CONTACT: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SKIN CONTACT: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention if person feels unwell. Take off contaminated clothing and wash it before use.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a doctor if person feels unwell.

INGESTION: If swallowed, immediately call a doctor. Do NOT induce vomiting.

SECTION 5 – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use water fog, alcohol foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

SPECIFIC HAZARDS: Vapors are heavier than air and may travel along the ground to a distant ignition source and flash back. See Section 10 for Stability and Reactivity. **NOTE:** EMPTY CONTAINERS CONTAIN COMBUSTIBLE VAPORS THAT CAN CAUSE FLASH FIRES

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Page 3 of 10

OR EXPLOSIONS. CONTAINERS ARE SINGLE-TRIP CONTAINERS AND SHOULD NOT BE USED FOR ANY REASON AFTER BEING EMPTIED. DO NOT USE CUTTING TORCH EQUIPMENT OR ANY OTHER FLAME OR OTHER SOURCES OF IGNITION ON ANY EMPTY CONTAINER.

PROTECTIVE EQUIPMENT AND PRECAUTIONS: Use standard protective equipment including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES: Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas. Eliminate all sources of ignition in the vicinity of the spill or released vapor. See Section 2 for Hazards Identification. See Section 4 for First Aid Measures. See Section 5 for Fire Fighting Information. See Section 8 for Personal Protective Equipment.

SPILL CONTAINMENT AND CLEAN-UP: Eliminate potential sources of ignition. Stop leak if it can be done without risk. Dike and contain spill. Do not touch or walk through spilled material. Prevent entry into waterways, sewer, basements or confined areas. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. A vapor suppressing foam may be used to reduce vapors. Local, state and federal laws and/or regulations may apply to releases and disposal of this material, as well as those materials and items employed in the clean-up releases. The user/responder will need to determine which local, state and federal laws and/or regulations are applicable. The National Response Center can be reached at 1-800-424-8802.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Avoid contact with eyes and skin. Use only with adequate ventilation. Use proper bonding and/or grounding procedures. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). Keep away from ignition sources such as heat, sparks, and flames. No smoking. Minimize exposure of product to air.

CONDITIONS FOR SAFE STORAGE: DO NOT USE OR STORE near heat, sparks, or flame. USE AND STORE ONLY IN A WELL-VENTILATED AREA. Handle containers with care. Keep container tightly closed when not in use. Store locked up.

STORAGE TEMPERATURE: -20°F to 100°F (-29°C to 38°C)

EMPTY CONTAINER WARNING: EMPTY CONTAINERS MAY CONTAIN COMBUSTIBLE VAPORS AND CAN BE DANGEROUS. SEE SECTION 5 FOR FIRE AND EXPLOSION HAZARD DATA.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

	CAS #	OSHA	ACGIH	NIOSH				Note
		PEL	TLV	STEL	REL	STEL	IDLH	
Petroleum Distillates	n/a	500 ppm	not est.	not est.	not est.	not est.	not est.	n/a
Hydroxy Alkoxylate	Proprietary	50 ppm	20 ppm	not est.	5 ppm	not est.	not est.	skin
Ethylbenzene	100-41-4	100 ppm	20 ppm	not est.	100 ppm	125 ppm	800 ppm (LEL)	n/a

ENGINEERING CONTROLS: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Local exhaust ventilation is recommended to control exposure.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

Eyes and Face: Eye protection such as safety glasses or chemical goggles is recommended if contact is likely.

Skin: Protective chemical/oil resistant clothing and gloves are recommended. Wear additional protective clothing as appropriate.

Respiratory: Wear a NIOSH/MSHA approved respirator as necessary.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Practice good housekeeping.

NOTE: These precautions are for room temperature handling.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid, straw yellow
Odor	Faint aromatic
Odor Threshold	Not available
pH	6-7
Melting point/Freezing point	Not available
Initial Boiling Point and Boiling Range	303°F; 151°C
Flash Point	118°F; 47.8°C
Evaporation Rate	Not available
Flammability	Not available
Upper / lower Flammability or Explosive Limits	Not available
Vapor Pressure	0.4 mmHg
Vapor Density	Not available
Specific Gravity (ASTM D4052)	0.91
Solubility	Not available

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Page 5 of 10

Partition Coefficient; n-octanol/water	Not available
Auto-ignition Temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Pour Point	<-157°F; <-105°C

SECTION 10 - STABILITY AND REACTIVITY

REACTIVITY: See Incompatible Materials below.

CHEMICAL STABILITY: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

CONDITIONS TO AVOID: Flames, high energy ignition sources, and elevated temperatures.

INCOMPATIBLE MATERIALS: May react with oxygen; strong acids, strong oxidizing agents, such as; chlorates, nitrates, peroxides, etc.; alkalis, nitric acid; sulfuric acid; sulfur oxides; reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides, products of incomplete combustion.

SECTION 11 - TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE

INGESTION	INHALATION	SKIN CONTACT	EYE CONTACT	SKIN ABSORPTION
	X	X	X	X

SYMPTOMS RELATED TO PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS: Breathing of high vapor concentrations may cause dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness. The vapor or fumes from this material may cause respiratory irritation. Breathing this material at elevated concentrations causes central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors, or convulsions, loss of consciousness, coma or death.

DELAYED AND IMMEDIATE EFFECTS AND CHRONIC EFFECTS FROM SHORT- AND LONG-TERM EXPOSURE: Repeated skin exposure to a component of this product may cause irritation, even a burn; may cause a more severe response on covered skin, such as under clothing or gloves. Inhalation exposure to a component of this product has caused fetotoxicity in the presence of maternal toxicity in animals.

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Page 6 of 10

NUMERICAL MEASURES OF TOXICITY

Note: the information provided below are estimates; testing of the product is not available.

Acute Oral Toxicity (ATE _{mix} estimate)	Acute Dermal Toxicity (ATE _{mix} estimate)	Acute Inhalation (ATE _{mix} estimate)
Does not meet criteria	669	3.46 (vapors)

SENSITIZATION: No information available.

MUTAGENICITY: No information available.

CARCINOGENICITY LISTINGS – the following chemicals are listed as indicated:

Component	List
Cumene	IARC, NTP
Ethylbenzene	IARC
Naphthalene	IARC, NTP

REPRODUCTIVE TOXICITY: No information available.

Teratogenicity/Embryotoxicity: Hydroxy Alkoxylate has caused fetotoxicity with maternal toxicity. This product contains a component of a complex mixture (Xylenes (1330-20-7)) that has been shown to cause teratogenicity and/or embryotoxicity.

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): Respiratory tract irritation.

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE): No information available

ASPIRATION HAZARD: Aspiration hazard identified.

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICITY: This material is expected to be toxic to aquatic organisms.

PERSISTENCE AND DEGRADABILITY: No information not available

BIOACCUMULATIVE POTENTIAL: No information not available

MOBILITY IN SOIL: No information not available

OTHER ADVERSE EFFECTS: No information not available

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Information: Disposal of unused product may be subject to RCRA hazardous waste regulations (40 CFR Part 261). Disposal of the used product may also be regulated as hazardous waste due to resulting mixture characteristics, mixture components or product use. Such changes to the product may result in different and/or additional hazardous waste codes. Potential RCRA waste code based on the product as shipped: D001 IGNITABILITY.

State or local laws may impose additional regulatory requirements regarding disposal. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

EMPTY CONTAINER WARNING: EMPTY CONTAINERS MAY CONTAIN COMBUSTIBLE VAPORS AND CAN BE DANGEROUS. SEE SECTION 5 FOR FIRE AND EXPLOSION HAZARD DATA.

SECTION 14 - TRANSPORTATION INFORMATION

The following part numbers are not regulated by DOT:

9216-06, 9216-09, 9225-06, 9225-09, 9280-06, 19216-06, 19216-09, 19225-06, 19280-06

SECTION 15 - REGULATORY INFORMATION

§14(a) Consumer Product Safety Act General Certificate of Conformity

Power Service Products, Inc. certifies that its products meet the statutory and regulatory requirements of the US Consumer Products Safety Act, the Federal Hazardous Substances Act, and the Poison Prevention Packaging Act of 1970, as applicable. The Power Service products are manufactured in the United States in Weatherford, Texas, unless otherwise indicated on the product label. The product manufacture lot code is stamped on the product container. This Certification is based upon a reasonable testing program conducted by Power Service Products, Inc. which includes a quality control program incorporating, as necessary, confirmation of compliance by component suppliers. Third-party testing is not required to certify compliance. Further details may be obtained by contacting the Power Service Products, Inc. EHS Manager or at 1-800-643-9089.

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200

TSCA STATUS:

All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

EPA SARA TITLE III CHEMICAL LISTINGS:

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Section 302 Extremely Hazardous Substances: None

Sections 311/ 312 Hazard Class:

Acute Health Effects: Yes Sudden Release of Pressure Hazard: No
Chronic Health Effects: Yes Reactivity Hazard: No
Fire Hazard: Yes

NFPA (NATIONAL FIRE PROTECTION ASSOCIATION) RATING:

HEALTH: 2
FIRE: 2
REACTIVITY: 0

Section 313:

Specific chemical information is being withheld as a Trade Secret. The following chemicals subject to the reporting requirements of EPCRA Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (40 CFR Part 372) may be present in this product at a concentration that does not exceed the specified upper weight percentage.

CAS Number	Chemical Name	Max %
n/a	Glycol Ether Category	70
100-41-4	Ethylbenzene	7.0

State or local laws may impose additional regulatory requirements for components of this material. It is the responsibility solely of the Employer to maintain compliance with State and Local reporting.

This product contains a chemical known to the state of California to cause cancer and/or birth defects or other reproductive harm: ethylbenzene, toluene, cumene, naphthalene.

SECTION 16 – OTHER INFORMATION

DATE OF PREPARATION / REVISION: June 3, 2016

NOTE regarding product labeling: The OSHA Hazard Communication Standard applies to hazardous chemicals known to be present in the workplace. However, the labeling and Safety Data Sheet requirements do not apply to consumer products when they are used in the workplace for the purposes intended by the manufacturer and the use results in a duration and frequency of exposure which is not greater than the range of exposures that could reasonably be experienced by consumers when used for the intended purpose. Power Service Products intends for product packaged in 1 gallon or smaller containers to be used by consumers and has labeled those containers as required under the Consumer Product Safety Commission regulations. Power Service Products intends for product packaged in containers larger than 1 gallon to be used in the workplace and has labeled those products as required by the OSHA Hazard Communication Standard. The Consumer Product Safety Commission and OSHA Hazard Communication Standard labeling requirements are different and variations between the consumer and industrial labels may

Revised: June 3, 2016

Supersedes: May 30, 2015

POWER SERVICE CLEAR-DIESEL FUEL AND TANK CLEANER

Page 9 of 10

occur. It is the employer's responsibility to purchase the appropriate product for use in the workplace.

The information contained herein is offered in good faith and is believed to be accurate based on the data available to us as of the date of MSDS preparation. The information in this document applies to this specific product as supplied. It may not be appropriate for this product if the product is used in combination with other materials. The information in this document is not intended to constitute product performance information. Some of the information presented and conclusions drawn herein are from sources other than direct test data on the product. No statement shall be construed as an endorsement of any product or process. The recommended industrial hygiene and safe handling procedures are believed to be valid in the context of the intended use as described in product labeling. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate. You are urged to obtain material safety data sheets for all products you buy, process, use or distribute, and are encouraged to advise those who may come in contact with such products of the information contained therein. Regulatory requirements are subject to change and may differ between locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. No warranty or guarantee is expressed or implied with respect to this product, the accuracy and sufficiency of the data or recommendations herein, or the results to be obtained from the use of this product. IN NO EVENT SHALL POWER SERVICE PRODUCTS, INC. BE LIABLE FOR ANY LOSS, CLAIM, DAMAGE OR LIABILITY OF ANY KIND, WHICH MAY ARISE FROM OR IN CONNECTION WITH THE INFORMATION CONTAINED IN THIS DOCUMENT OR FROM THE USE, HANDLING OR STORAGE OF THE PRODUCT BY THE BUYER/USER, WHETHER DIRECT, INDIRECT, OR CONSEQUENTIAL, OR FOR ANY CLAIM BY ANY THIRD PARTY, BEYOND THE PURCHASE PRICE OR REPLACEMENT OF THE PRODUCT IN CONNECTION WITH WHICH SUCH LOSS, CLAIM, DAMAGE OR LIABILITY AROSE.

THE FOREGOING LIMITATIONS APPLY REGARDLESS OF THE CAUSES OR CIRCUMSTANCES GIVING RISE TO SUCH LOSS, CLAIM, DAMAGE OR LIABILITY, EVEN IF SUCH LOSS, CLAIM, DAMAGE, OR LIABILITY IS BASED ON NEGLIGENCE OR OTHER TORTS OR BREACH OF CONTRACT.