

# Fire Control Fire Extinguisher (FC340M-VB)

Part number 466425

Multipurpose use

Rechargeable

**UL Rated 3-A, 40-B:C**



For use on the following types of fire:



## Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The FC340M-VB unit is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum and a tough metal valve assembly.

Supplied with metal retention bracket.

## At a Glance

- Model FC340M-VB
- Multipurpose Dry Chemical
- UL listed
- UL rated 3-A, 40-B:C
- Supplied with retention bracket
- Monoammonium Phosphate
- 6 year limited warranty
- Suitable for use on most common fires

## Features

- Easy-to-read gauge tells you fire extinguisher is charged and ready for use
- Clear instruction label using graphics to show steps required to operate extinguisher
- Easy-to-pull safety pin
- Tough impact resistant metal valve, handle & lever
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty



Pt # 466425 - 4 pack

Pt # 46642527 - 4 pack Navistar

Pt # 46642525 - 4 pack Balkamp

UPC: 0-47871-66425-2

I2F: 20047871664256

Pt # 46642521 - 4 pack Carquest

UPC: 0-47871-42521-1

I2F: 10047871425218

Pt # 21006446 - 4 pack Grainger

UPC: 0-47871-66425-2

I2F: 10047871664259

## Product Specification

Net agent weight (Average)	5.5 lb.
Unit weight (Average)	8.4 lb.
Diameter	4.5 inches
Height	16.88 inches
Discharge time	13-15 seconds
Discharge range	12-18 feet
Operating pressure	195 psi
Cylinder	Seamless aluminum
Valve, handle, lever	Metal
Strap Bracket	U.S.C.G approved

## Packaging Options



**MASTER PACK**

Packaging dimensions (inches)

	Depth	Width	Height
Carton	4.75	6.0	17.0
Master Pack	13.0	17.25	9.87



Kidde Residential and Commercial Division  
1016 Corporate Park Drive, Mebane, NC 27302  
(800) 880-6788 [www.Kidde.com](http://www.Kidde.com)